

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently amended) A liquid crystal display comprising:

a housing ~~(10)~~;

a liquid crystal cell functioning as display, disposed  
5 on said housing;

a ~~support 2~~, plastic support configured as reflector;  
and,

a heating device for the ~~display (1)~~, the display, the  
heating device including a metallic layer ~~(8)~~ applied directly  
10 onto the ~~support (2)~~ support, the metallic layer being formed  
by coating the plastic support with a primer bonding layer  
followed by a subsequent galvanic coating.

2. (Canceled)

3. (Currently amended) ~~The~~ A display apparatus  
~~according to claim 1, wherein comprising:~~

a housing;

a liquid crystal cell functioning as display and disposed  
5 on said housing;

a support configured as reflector; and,

a heating device for the display, the heating device  
including a metallic layer applied directly onto the support,  
the metallic layer ~~(8)~~ is being a foil coated with a galvanic  
10 bonding layer by deep-drawing and connected with the support  
by rear-spraying of the foil.

4. (Previously presented) The display apparatus according to claim 3, wherein:

the galvanic coating is copper.

5. (Currently amended) The display apparatus according to claim 1, wherein:

the support ~~(2)~~ consists of metal-coatable and metal non-coatable plastic, and the metal-coatable plastic is in part  
5 chemically metallized.

6. (Currently amended) The display apparatus according to claim 1 further including at least one of:

contact pins ~~(12)~~ injected into the support ~~(2)~~ contacting the metallic layer ~~(8)~~; and,  
5 metallized plastic surfaces soldered together with a conductor plate.

7. (Currently amended) The display apparatus according to claim 1 wherein:

the housing ~~(20)~~ and the support ~~(2)~~, equipped with the metallic layer ~~(8)~~ as heating device, are a single-piece  
5 component.

8. (Currently amended) The display apparatus according to claim 1, wherein:

the plastic support ~~(2)~~ is irradiated with a short-wave ultra-violet light of an excimer lamp or an excimer laser and  
5 immersed in a watery solution.

9. (Currently amended) The display apparatus according to claim 8, further including:

a galvanic reinforcement of the metallic layer ~~(8)~~.

10. (New) The display apparatus according to

claim 1, wherein the galvanic coating is copper.

11. (New) The display apparatus according to claim 3 further including at least one of:

contact pins injected into the support contacting the metallic layer; and,

5 metallized plastic surfaces soldered together with a conductor plate.

12. (New) The display apparatus according to claim 3, wherein the housing and the support, equipped with the metallic layer as heating device, are a single-piece component.

13. (New) A method of forming a heated liquid crystal display comprising:

providing a liquid crystal cell functioning as a display;

providing a plastic support configured as a reflector and

5 being adapted to receive said liquid crystal cell; and

applying a metallic layer directly onto said support as  
a heating device for heating said liquid crystal cell, the  
applying including coating selected portions of the plastic  
support with a primer bonding layer and then subsequently  
10 galvanic coating the primer bonding layer.

14. (New) A method of forming a heated liquid crystal display comprising:

providing a liquid crystal cell functioning as a display;

providing a plastic support configured as a reflector and

5 being adapted to receive said liquid crystal cell; and

applying a metallic layer directly onto said support as  
a heating device for heating said liquid crystal cell, the  
applying including coating a foil with a primer layer,  
subjecting the foil to a galvanic treatment, deep-drawing the

- 6 -

10 foil, and connecting he foil with the plastic support by rear-spraying.